

Nylon Cable Ties 尼龍扎綫帶

Mounted Head Cable Ties 固定头式扎线带

Description


The Mounted Head Cable Tie can be screwed on or bolted down in order to secure the bundled harness to panels or other surfaces. It can be repositioned before final assembly.

Application

This range of cable ties has a mounting hole fixing method. Once fastened around the cables the bundle can be simply secured to the panel with a screw or bolt.

Ideal for fixing cables, pipes and hoses onto solid surfaces with pre drilled holes or holes in metal plates.


These ties are used in many industries, for example: building construction, panel builders and white goods manufacturers.



Available Size



Part No. 货号	Item Code 型号	Length 长度	Width 宽度	Mounting Hole DIA. 螺孔尺寸	Mini Tensile Strength 最小拉力	Maxi Bundle Diameter 最大捆扎范围
		mm	mm	Ø(mm)	lbs Kg	mm
5890	Q100I-MH	100	3.5	4.2	40 18	22
5892	Q150I-MH	150	3.5	4.2	40 18	32
5894	Q190S-MH	190	4.7	5.2	50 22	45
5896	Q300S-MH	300	4.7	5.2	50 22	70



Saddle Mounting Ties 固定锁式扎线带

Available Size



Part No. 货号	Item Code 型号	Length 长度	Width 宽度	Mini Tensile Strength 最小拉力	Maxi Bundle Diameter 最大捆扎范围
		mm	mm	lbs Kg	mm
5900	Q165-SMT	165	7.5	50 22	33

Note: Fixing the tie with CTH-3 (see Page 22)

